

## PIR Occupancy Sensor LENS DATASHEET









IR-TEC's TRANS and OS-NET PIR based Occupancy Sensors feature with interchangeable lens options. Each lens provides different sensing coverage which varies with the actual mounting height.

The specified detection coverage and mounting height of each lens are based on the test result of human motion walking across the detection zones. The actual coverage may be reduced if the motion is moving toward or away the sensor. High ambient temperature (above 82°F/28°C) could reduce the coverage of PIR sensor. If ambient temperature at the covered area are expected to be high sometimes, consider adding more sensors or reduce the mounting height, if possible.

The followings are all available lens options and their respective detection patterns at printing time. For details of latest lens options available, please visit [www.irtec.com](http://www.irtec.com).















### LENS OPTIONS

	Lens		Shape	Recommended Mounting Height		Coverage
A		Standard	Cone	8~15 ft.	2.4~4.5m	2X height
B		Extra wide	Cone	8~10 ft.	2.4~3.0m	6X height
C		High bay	Cone	15~30 ft.	4.5~9.0m	3X height
D		Standard	Round flat	8~20 ft.	2.4~6.0m	2X height
F		Extra wide	Dome	8~20 ft.	2.4~6.0m	4X height
G		Aisle way	Arch	8~40 ft.	2.4~12.0m	3X height
H		High bay	Dome	30~50 ft.	9.0~15.0m	1X height
L		Long aisle	Arch	8~10 ft.	2.4~3.0 m	6X height



#### NOTE:

- Lens G/L can be rotated to change the direction of coverage. Its 3X/6X height coverage refers only to the total length, the width of coverage will vary with the mounting height (see table of Lens G/L section). This lens is not IP-66 rated.
- Lens C/G may be mounted up to 40/50 ft. (12/15m) or higher at the area, providing with large moving object such as forklift trucks. Before installing all sensors, please ensure that the sensor can have optimal detection at desired height.
- All dimensions are for reference only.



LENS A		2X Standard						
		Mounting Height	m (ft.)	2.4 (8)	3.0 (10)	3.6 (12)	4.5 (15)	
		Max. Coverage Ø	m (ft.)	4.8 (16)	6.0 (20)	7.2 (24)	9.0 (30)	
		Minor Motion Ø	m (ft.)	3.0 (10)	1.8 (6)	1.8 (6)	--	
								
LENS B		6X Extra wide						
		Mounting Height	m (ft.)	2.4 (8)	2.6 (8.5)	2.8 (9)	3.0 (10)	
		Max. Coverage Ø	m (ft.)	14.4 (48)	15.6 (51)	16.8 (54)	18.0 (60)	
								
LENS C		3X High bay						
		Mounting Height	m (ft.)	4.5 (15)	6.0 (20)	8.0 (26)	9.0 (30)	
		Max. Coverage Ø	m (ft.)	13.5 (45)	18.0 (60)	24.0 (78)	27.0 (90)	
								
LENS D		2X Standard						
		Mounting Height	m (ft.)	2.4 (8)	3.0 (10)	4.5 (15)	6.0 (20)	
		Max. Coverage Ø	m (ft.)	4.8 (16)	6.0 (20)	9.0 (30)	12.0 (40)	
		Minor Motion Ø	m (ft.)	1.8 (6)	3.0 (10)	--	--	
								

## LENS F 4X Extra wide

Mounting Height	m (ft.)	2.4 (8)	3.0 (10)	4.5 (15)	6.0 (20)
Max. Coverage Ø	m (ft.)	9.6 (32)	12.0 (40)	18.0(60)	24.0 (80)
Minor Motion Ø	m (ft.)	1.8 (6)	4.0 (13)	--	--






Top View





## LENS G 3X Aisle way

Mounting Height	m (ft.)	3.0 (10)	6.0 (20)	9.0 (30)	12.0 (40)
Max. Coverage Ø	m (ft.)	9.0 x 4 (30 x 13)	18.0 x 4 (60 x 13)	27.0 x 4 (90 x 13)	36.0 x 4 (120 x 13)

For indoor use only.





Top View






## LENS H 1X High bay

Mounting Height	m (ft.)	9.0 (30)	11.0 (36)	13.0 (43)	15.0 (49)
Max. Coverage Ø	m (ft.)	9.0 (20)	11.0 (36)	13.0 (43)	15.0 (49)




Top View




<b>LENS L</b> 6X Long aisle For indoor use only. 	Mounting Height	m (ft.)	2.4 (8)	2.6 (8.5)	2.8 (9)	3.0 (10)
	Max. Coverage Ø	m (ft.)	14.4 x 2 (48 x 6.5)	15.6 x 2 (51 x 6.5)	16.8 x 2 (54 x 6.5)	18.0 x 2 (60 x 6.5)

Top View




Side View





## ACCESSORIES

**LENS HOOD** Lens hood is designed to prevent the ambient light sensor from being saturated by excessive lighting nearby.

### LH-110




### LH-068




## LENS MASK

### LM-12C For Lens A/B/C




### LM-12D For Lens F



① Push the mask onto the installed lens


Click!



② Masked area can be changed by rotating the mask

### Example: Lens F with LM-12D

Top View



#### Coverage Area with Lens F and Mask

Mounting Height	m (ft.)	2.4 (8)	3.0 (10)	4.5 (15)	6.0 (20)
Max. Coverage Length x Width	m (ft.)	9.6 x 2 (32 x 6.5)	12.0 x 2 (40 x 6.5)	18.0 x 2 (60 x 6.5)	24.0 x 2 (80 x 6.5)

If necessary, the masked area can be altered by cutting off the respective grooved segments with a wire cutter or knife.

